



### Specialties for Copper and Steel/PVC pipe

- Hot/Wet Tap Saddles/Sleeves/Equipment
- Line Stop Saddles/Sleeves/Equipment/Sealing Elements
- Pipe Freezing Kits – CO2 and LN2
- Insta-Clamp Solder Joint Repair Clamp
- Xtra Deep and Specialty Hole Saws
- Pipe Repair Clamps, Roll Groovers and more...

## JCM 106 Bell Joint Leak Clamp Steel/PVC

NOM. PIPE SIZE (IN.)	PIPE O.D. SIZE (IN.)	MAXIMUM BELL O.D. (IN.)	MAXIMUM LIP O.D. (IN.)	OVERALL LENGTH*	MAX.STD. CPLG. LENGTH	CATALOG NUMBER	PRICE EACH	APPROX. WEIGHT EACH (LBS.)
4	4.50	6.13	5.43	11-1/2	7	106-0450	<b>\$ 295.50</b>	12
6	6.63	8.25	7.56	11-1/2	7	106-0663	<b>\$ 321.40</b>	17
8	8.63	10.88	9.56	11-1/2	7	106-0863	<b>\$ 444.25</b>	21

\* Dimensions will change with the use of studs

Sizes available for PVC Rubber Joint Bells - Std Steel Sizes (SDR26, SDR21) 4.00" to 8.00"  
Sizes Available for Standard Steel Threaded Couplings 4.00" to 8.00"

### Specifications:

- **Body:** Ductile Iron per ASTM A536
- **Bolts & Nuts:** Epoxy Coated Bolts Powercron 590-534 corrosion resistant low alloy
- **Coating:** Ductile Iron components furnished with corrosion resistant shop coat primer
- **Gasket:** Virgin SBR - Compounded for use with water, salt solutions, mild acids and bases
- **Temperature Range:** from -40° to 150° F (-40° to 65° C) constant, max intermittent 180° F